



Date of Issue: 6/4/2025 Report Number: 25-001500

Revision Number:1

Date Order Received: 05/30/2025

For the Account of: Gabriel A/S Hjulmagervej 55

Client's Identification: HARLEQUIN

CERTIFICATE OF TESTING

TEST PERFORMED: Smolder Resistance of Materials Used in Upholstered Furniture - Section 1: Cover Fabrics California Technical Bulletin 117-2013 (January 2019 Revision)

TEST RESULTS

	Specimen	Char Length (in)	Extinguished in 45 Minutes
Initial Test	1	0.6	Υ
	2	0.7	Υ
	3	0.7	Υ

9000 Aalborg Denmark

NOTES

Test Conditions: 70 ±5°F, 50 ±5% Relative Humidity Requirement 70±5°F, less than 55% Relative Humidity

Sampling: As Received Ignition Source: SRM 1196a

Abbreviations: SE = Self-extinguished OBV = Obvious ignition of substrate

ACCEPTANCE CRITERIA

A material is considered to pass or fail based on the following criteria:

- 1. A single mock-up test specimen fails to meet the requirements of this test procedure if any of the following criteria occurs:
 - a. The mock-up test specimen continues to smolder after the 45 minute test duration
 - b. A vertical char length of more than 1.8 inches (45mm) develops on the cover fabric
 - c. The mock-up test specimen transitions to open flaming
- 2. The cover fabric passes the test if three initial mock-up specimens pass the test, i.e. the cigarettes burn their full length and are no longer smoldering
- 3. If more than one initial specimen fails, the cover fabric fails the test
- 4. If any one of the three initial specimens fails, repeat the test on additional three specimens
- 5. If all three additional specimens pass the test, the cover fabric passes the test. If any one of the additional three specimens fails, the cover fabric fails the test

CONCLUSION	Based on the above Results and Acceptance Criteria, the item tested is: ☑ Pass ☐ Fail
	ertify that the above results were obtained after testing specimen in accordance with the procedures and equipment industry and stated above.
Berta Stive	en e

553 76th Street, Byron Center, MI 49315

Authorized Signature

P: 616-559-6123 E: contact@applied-lab.com

Page 1 of

Date Order Completed: 06/04/2025